



SPECIAL OPERATIONS VECTOR 3 HH-Series Harness/Container

The Special Operations Vector Harness/Container (SOV3-HH) is designed for HAHO-HALO operations allowing a single operator to carry a full compliment of weapons and combat equipment utilizing state of the art technologies, making the SOV3-HH a versatile and essential parachute system for training and operational requirements.

Three (3) Deployment Methods

The SOV3-HH, with minimal reconfiguration, can support up to three (3) different deployment applications to fit your ever-changing mission parameters.

- 1 Double Bag Static Line (DBSL)
- 2 BOC Hand-Deploy
- 3 Over-the-Shoulder (OTS) Ripcord

SOV3-HH Options

- Fully adjustable harness with pulley-style main lift web
- Adjustable diagonals, chest, leg straps and waistband
- Six (6) or Eight (8) cargo attachment points
- Seat sling attachment points
- Adjustable leg strap hardware (B-12 or QE Snaps)
- Zipper attachments for oxygen & utility pouches
- Skyhook RSL with integrated Collins Lanyard
- Ballistic cloth leg pad covers

Additional Specifications

- Minimum shelf life 4.5 years
- Minimum Service Life 12 years
- Combined Service Life 16.5 years
- Maintainable by MOS Rigger Personnel
- Harness Fits 5th to 95th Percentile Parachutist (MIL-STD 1472)



PRODUCT SPECIFICATIONS

SOV3 HAHO/HALO

SOV3-HH Harness Container

Maximum Suspended Weight*	450 lb (205 kg)	
Minimum Deployment Altitude Main Parachute**	2,000 - 3,000 ft (610 - 914 m)	
Minimum Deployment Altitude Reserve Parachute**	1,500 - 2,000 ft (457 - 610 m)	
Maximum Deployment Altitude**	35,000 ft (10,668 m)	
Canopy Alternatives	280 - 360 sq ft (25 - 33 sq m)	
Physical Dimensions	22 x 15 x 5.5 in - 23.5 x 15 x 7 in (56 x 38 x 14 cm) - (60 x 38 x 18 cm)	
Harness / Container Weight	30 - 35 lb (13 - 16 kg)	
Reserve AAD Setup	Control unit installed under reserve pin flap or on ring cover	
Reserve Static Line	Skyhook RSL with reserve pin attached to lanyard or Mod-A RSL with RW-4 ring attached to lanyard - both with integrated Collins Lanyard	
Main Risers	3-Ring, Type 7 with Front Riser Trim Tabs Hard Housing Channels	
Main Toggles	11 in (28 cm) HAHO toggles with HAHO extensions	
Harness Configuration	Fully Adjustable MLW, Diagonals, Chest & Leg Straps, Bellyband	
Leg Strap Hardware	Interchangeable and Adjustable B-12 or Quick Ejector - other types optional	
Configurations	HH 6-Ring	HH 8-Ring
Attachment Points	Six (6) cargo attachment points	Eight (8) cargo attachment points
Handle Locations	In-board emergency handles	Out-board emergency handles
Main Deployment Type / Activation	Over-the-Shoulder Ripcord BOC Hand-Deploy, Double Bag Static Line	BOC Hand-Deploy Double Bag Static Line
Container Material	1000 Denier Cordura®	
Colors	Black, silver, smoke, navy blue, olive drab green, woodland/digital camouflage, desert camouflage - other colors are available on request	
Compatible Oxygen Systems	Twin 22 or 53 cu in, single 80, 88, 120 or 122 cu in	
Special Equipment Interfaces	Zip-On Side Pouches for Oxygen, Radio or Utility Use Seat Sling, Cargo Attachment Points	

* Dependent on main and reserve canopy model and deployment system

** Dependent on canopy choice, deployment system and Skyhook option

Complete Parachute Solutions, Inc.

1320 E. International Speedway Blvd., Suite 1, DeLand, FL 32724 USA
Tel: +1 386 736-3862 Fax: +1 386 736-3899
Email: info@cpsworld.com
www.cpsworld.com

COMPLETE PARACHUTE SOLUTIONS

CPS