

BATTERY COVER With Integrated Air Filter

INSTALLATION GUIDE

Part Number: 9603 | NSN: 6160-22-622-4689



Using a 2,0 1,4Nm HEX screwdriver, loosen the 4 mounting screws for the wrist mount. Place removed wrist mount in a secure location for reassembly.
(The screws are locked in the wrist mount by means of locking washers)



Remove the 4 screws that hold down the battery cover/filter. DO NOT REMOVE the red centered screws. ONLY REMOVE the 4 screws on the battery cover/filter.



Lift the battery cover/filter STRAIGHT UP so as not to create the rubber gasket. MAKE SURE that no dirt, moisture or any other foreign objects get into the interior space of the unit.

!!! WARNING !!! PLEASE READ

Over tightening the screws could damage the altimeter! Damaging the inner gasket seal may prevent the altimeter from being watertight. Not replacing all screws could allow foreign objects to enter the unit and damage it. BE CAREFUL to disassemble and reassemble this altimeter properly to ensure proper functionality.



4 INSPECT UNDER THE RUBBER GASKET for any dirt, moisture or any other foreign materials. REMOVE any unwanted particles using compressed air or lint-less brush.



5 REPLACE old cover/filter with new one. COVER/FILTER MUST BE PLACED on the unit CAREFULLY!!! Cover/Filter must be installed by lowering it STRAIGHT DOWN so it doesn't crease, move, damage or alter the gasket.



SCREW INSTALLATION

After the cover is properly aligned with the body of the altimeter, start each screw before tightening. Once ALL screws are started, use the 2,0 - 1,4Nm HEX screwdriver to tighten each screw 1,4Nm. **DO NOT OVER TIGHTEN!** REPEAT steps to reassemble wrist mount.